

MediaTac™

PSA26
12μ

Product Description

MediaTac™ is a 12μ (0.5 mil) clear polyester mounting film coated on both sides with a pressure sensitive, aqueous acrylic adhesive, one of which is protected by a bleached clay coated Kraft paper siliconised on both sides with a differential release. The adhesive on the other side of the film is exposed and self-wound onto the roll. Available in various sizes.

Applications

MediaTac™ is developed for photo-labs where a high grade of moisture stability within the mounting film is required. MediaTac™ is ideal for high volume mounting, including the pre-coating of boards and for image decal applications. MediaTac™ is perfect for mounting prints to smooth porous substrates such as White Display Board, foam centred boards, Gatorfoam™ and tempered hardboard.

Product Structure

Adhesive Layer:	Aqueous Acrylic (Pressure Sensitive)	62μ (2.5 mil)
Film:	12μ Clear Polyester	
Adhesive Layer:	Aqueous Acrylic (Pressure Sensitive)	
Release Liner:	Clay Coated 2 Side Siliconised Kraft Paper	

General Properties

Film Thickness	12μ (0.5 mil)
Adhesive Layer	25μ (1 mil) on each side of the film
Outdoor Durability	n/a
UV Protection Factor	n/a
pH level	Neutral
Application Temperature	>5°C
Service Temperature Range	-20°C to 120°C
Shelf Life	Use within 1 year after opening original box.
Storage Conditions	15°C to 22°C ; 50 to 55% Relative Humidity

Process Settings

Roller Laminator	Vacuum Press
Temp: Room temp to 40°C (104°F) Speed: 0.3m to 2.5m (1ft to 8ft) per minute	n/a

Specifications subject to change without notice.

Published information concerning Drytac products is based upon research which the company believes to be reliable and accurate. Such information is intended only as a guide and is given without guarantees. Purchasers should independently determine, prior to use, the suitability of each material for their specific purpose. Drytac does not accept liability for risks associated with the performance of the materials in application. All Drytac products are subjected to careful quality control throughout the manufacturing process and are sold subject to Drytac standard conditions of sale.

Drytac Europe Ltd (UK) - Drytac House, Filwood Road, Fishponds, Bristol, BS16 3RY, UK. Tel: +44 (0) 845-070-0660
Drytac Corp. (USA) - 5601 Eastport Boulevard, Richmond, Virginia 23231, USA. Telephone: 1-800-603-6610
Drytac Canada Inc. (Canada) - 105 Nuggett Court, Brampton, Ontario L6T 5A9, CA. Telephone 001-9056-601-748